

IN THE CLAIMS:

1 1. A piston-chamber combination comprising an elongate chamber which is
2 bounded by an inner chamber wall and comprising a piston in said chamber to be
3 sealingly movable relative to said chamber at least between first and second longitudinal
4 positions of said chamber,

5 said chamber having cross-sections of different cross-sectional areas at the first
6 and second longitudinal positions of said chamber and at least substantially continuously
7 different cross- sectional areas at intermediate longitudinal positions between the first and
8 second longitudinal positions thereof, the cross-sectional area at the first longitudinal
9 position being larger than the cross-sectional area at the second longitudinal position,

10 said piston including a piston body and sealing means supported by the piston
11 body for sealing on said inner chamber wall, the piston body being designed to adapt
12 itself and said sealing means to said different cross-sectional areas of said chamber during
13 the relative movements of said piston from the first longitudinal position through said
14 intermediate longitudinal positions to the second longitudinal position of said chamber.

1 2. A combination according to claim 1, wherein the cross-sectional area of
2 said chamber at the second longitudinal position thereof is between 95% and 15% of the
3 cross-sectional area of said chamber at the first longitudinal position thereof.

1 3. A combination according to claim 1, wherein the cross-sectional area of
2 said chamber at the second longitudinal position thereof is 95-70% of the cross-sectional
3 area of said chamber at the first longitudinal position thereof.

a1

10030243 100201

1 4. A combination according to claim 1, wherein the cross-sectional area of
2 said chamber at the second longitudinal position thereof is approximately 50% of the
3 cross-sectional area of said chamber at the first longitudinal position thereof.

1 5. A combination according to claim 1, wherein the piston comprises:
2 a plurality of at least substantially stiff support members rotatably fastened to a
3 common member,
4 elastically deformable means, supported by said supporting members, for sealing
5 against the inner wall of the chamber said support members being rotatable between 10°
6 and 40° relative to the longitudinal axis of the chamber.

1 6. A combination according to claim 5, wherein the support members are
2 rotatable so as to be at least approximately parallel to the longitudinal axis.

1 7. A combination according to claim 5, wherein the common member is
2 attached to a handle for use by an operator, and wherein the support members extend, in
3 the chamber, in a direction relatively away from said handle.

1 8. A combination according to claim 5, further comprising means for biasing
2 the support members against the inner wall of the chamber.

1 9. A combination according to any of Claim 1, wherein the piston comprises
2 an elastically deformable container comprising a deformable material.

1 10. A combination according to claim 9, wherein the deformable material is a
2 fluid or a mixture of fluids from the group of water, steam, gas, or foam.

10030242 100201

a1

1 11. A combination according to claim 9, wherein, in a cross-section through
2 the longitudinal direction, the container, when being positioned at the first longitudinal
3 position of the chamber, has a first shape which is different from a second shape of the
4 container when being positioned at the second longitudinal position of said chamber.

1 12. A combination according to claim 11, wherein at least part of the
2 deformable material is compressible and wherein the first shape has an area being larger
3 than an area of the second shape.

1 13. A combination according to claim 11, wherein the deformable material is
2 substantially incompressible.

1 14. A combination according to claim 9, wherein the container is inflatable.

1 15. A combination according to any of claim 9, wherein the piston comprises
2 an enclosed space communicating with the deformable container, the enclosed space
3 having a variable volume.

1 16. A combination according to claim 15, wherein the volume is manually
2 adjustable.

1 17. A combination according to claim 15, wherein the enclosed space
2 comprises a spring-biased pressure tuning piston.

1 18. A combination according to Claim 15, further comprising means for
2 defining the volume of the enclosed space so that the pressure of fluid in the enclosed
3 place chamber relates to the pressure acting on the piston when being positioned at the
4 second longitudinal position of the chamber.

1 19. A combination according to claim 18, wherein the defining means are
2 adapted to define the pressure in the enclosed space at least substantially identical to the
3 pressure acting on the piston when being positioned at the second longitudinal position of
4 the chamber.

1 20. A combination according to Claim 1, wherein the cross-sections of the
2 different cross-sectional areas have different cross-sectional shapes, the change in cross-
3 sectional shape of the chamber being at least substantially continuous between the first
4 and second longitudinal positions of the chamber, wherein the piston is further designed
5 to adapt itself and the sealing means to the different cross-sectional shapes.

1 21. A combination according to claim 20, wherein the cross-sectional shape of
2 the chamber at the first longitudinal position thereof is at least substantially circular and
3 wherein the cross-sectional shape of the chamber at the second longitudinal position
4 thereof is elongate, such as oval, having a first dimension being at least 2 times a
5 dimension at an angle to the first dimension.

a1

100304242001

22. A combination according to claim 20, wherein the cross-sectional shape of the chamber at the first longitudinal position thereof is substantially circular and wherein the cross-sectional shape of the chamber at the second longitudinal position thereof comprises two or more substantially elongate parts.

23. A combination according to Claim 20, wherein a first circumferential length of the cross-sectional shape of the cylinder at the first longitudinal position thereof amounts to 80-120% of a second circumferential length of the cross-sectional shape of the chamber at the second longitudinal position thereof.

24. A combination according to claim 23, wherein the first and second circumferential lengths are at least substantially identical.

25. A combination according to Claim 1, wherein the piston comprises:
an elastically deformable material being adapted to adapt itself to the different cross-sectional areas of the chamber between the first and second longitudinal positions thereof, and

a coiled flat spring having a central axis at least substantially along the longitudinal axis of the chamber, the spring being positioned adjacently to the elastically deformable material so as to support the elastically deformable material in the longitudinal direction.

100304-1004

1 26. A combination according to claim 25, wherein the piston further
2 comprises a number of flat supporting means positioned between the elastically
3 deformable material and the spring, the supporting means being rotatable along an
4 interface between the spring and the elastically deformable material.

1 27. A combination according to claim 26, wherein the supporting means are
2 adapted to rotate from a first position to a second position wherein, in the first position,
3 an outer boundary thereof may be comprised within the cross-sectional area of the
4 chamber in the first longitudinal position thereof and wherein, in the second position, an
5 outer boundary thereof may be comprised within the cross-sectional area of the chamber
6 in the second longitudinal position thereof.

1 28. A combination according to Claim 9, wherein the container comprises an
2 elastically deformable material comprising reinforcement means.

1 29. A combination according to Claim 1 comprising a hose to form the piston,
2 the hose, when being positioned at the first longitudinal position of the chamber, having
3 substantially the shape of a cone with the larger diameter thereof facing the second
4 longitudinal position of the chamber.

1 30. A combination according to claim 29, wherein the hose comprising
2 reinforcement windings having a braid angle which is different from $54^{\circ}44'$.

1 31. A combination according to claim 28, wherein the reinforcement means
2 comprises fibers.

20250124 10:24:01

1 32. A combination according to Claim 9, wherein the foam or fluid is adapted
2 to provide, within the container, a pressure higher than the highest pressure of the
3 surrounding atmosphere during translation of the piston from the first longitudinal
4 position of the chamber to the second longitudinal position thereof or vice versa.

1 33. A piston-chamber combination comprising an elongate chamber bounded
2 by an inner chamber wall and comprising a piston in the chamber to be sealingly movable
3 in the chamber,

4 the piston being movable in the chamber at least from a first longitudinal position
5 thereof to a second longitudinal position thereof,

6 the chamber comprising an elastically deformable inner wall along at least part of
7 the length of the chamber wall between the first and second longitudinal positions,

8 the chamber having, at the first longitudinal position thereof when the piston is
9 positioned at that position, a first cross-sectional area, which is larger than a second cross-
10 sectional area at the second longitudinal position of the chamber when the piston is
11 positioned at that position, the change in cross-sections of the chamber being substantially
12 continuous between the first and second longitudinal positions when the piston is moved
13 between the first and second longitudinal positions.

1 34. A combination according to claim 33, wherein the piston is made of a
2 substantially incompressible material.

1 35. A combination according to Claim 33, wherein the piston has, in a cross
2 section along the longitudinal axis, a shape tapering in a direction from the first
3 longitudinal position of the chamber to the second longitudinal position thereof.

1003034-10001

21

1 36. A combination according to claim 35, wherein the angle (ξ) between the
2 wall and the central axis of the cylinder is at least smaller than the angle (v) between the
3 Wall of the taper of the piston and the central axis of the chamber.

1 37. A combination according to Claim 33, wherein the chamber comprises:
2 an outer supporting structure enclosing the inner wall and
3 a fluid held by a space defined by the outer supporting structure and the inner
4 wall.

1 38. A combination according to claim 37, wherein the space defined by the
2 outer structure and the inner wall is inflatable.

1 39. A combination according to claim 33, wherein the piston comprises an
2 elastically deformable container comprising a deformable material and designed
3 according to Claim 11.

a1

TO 3307 242000

40. A pump for pumping a fluid, the pump comprising:
a combination according to Claim 1,
means for engaging the piston from a position outside the chamber,
a fluid entrance connected to the chamber and comprising a valve means, and
a fluid exit connected to the chamber.

ai 41. A pump according to claim 40, wherein the engaging means have an outer
position where the piston is at the first longitudinal position of the chamber, and an inner
position where the piston is at the second longitudinal position of the chamber.

42. A pump according to claim 40, wherein the engaging means have an outer
position where the piston is at the second longitudinal position of the chamber, and an
inner position where the piston is at the first longitudinal position of the chamber.

43. A shock absorber comprising:
a combination according to Claim 1,
means for engaging the piston from a position outside the chamber, wherein the
engaging means have an outer position where the piston is at the first longitudinal
position of the chamber, and an inner position where the piston is at the second
longitudinal position.

44. A shock absorber according to claim 43, further comprising a fluid
entrance connected to the chamber and comprising a valve means.

45. A shock absorber according to claim 43, further comprising a fluid exit
connected to the chamber and comprising a valve means.

1 46. A shock absorber according to any of claim 43, wherein the chamber and
2 the piston form an at least substantially sealed cavity comprising a fluid, the fluid being
3 compressed when the piston moves from the first to the second longitudinal positions of
4 the chamber.

1 47. A shock absorber according to Claim 43, further comprising means for
2 biasing the piston toward the first longitudinal position of the chamber.

21
1 48. An actuator comprising:
2 a combination according to Claim 1,
3 means for engaging the piston from a position outside the chamber,
4 means for introducing fluid into the chamber in order to displace the piston
5 between the first and the second longitudinal positions of the chamber.

1 49. An actuator according to claim 48, further comprising a fluid entrance
2 connected to the chamber and comprising a valve means.

1 50. An actuator according to claim 48, further comprising a fluid exit
2 connected to the chamber and comprising a valve means.

1 51. An actuator according to Claim 48, further comprising means for biasing
2 the piston toward the first or second longitudinal position of the chamber.

1 52. An actuator according to claim 48, wherein the introducing means
2 comprise means for introducing pressurized fluid into the chamber.